



Moose Sports Surfaces, Ltd.
2257 North Wayne Avenue, Suite 2C
Chicago, Illinois 60614
773.477.4664
773.477.8248 *fax*
www.mooseports.com

GAMECOURT®
SYNTHETIC FLOORING CARE & MAINTENANCE GUIDE
Revised 04-09-09

The GAMECOURT® polyurethane synthetic flooring system, like all quality floor surfaces requires consistent cleaning and scheduled maintenance to ensure that it stays looking great. The schedule for cleaning depends on many factors including – various activities, how often the floor is used, and the volume of foot traffic on the floor. The more consistent the cleaning schedule, the better the appearance of the floor. The following general guidelines will help to keep your new GAMECOURT® floor looking great.

- 1) Stay off your new GAMECOURT® floor for 1 week after the completion date so the top coat finish can fully cure.
- 2) Keep the surface of the GAMECOURT® system clean. Dust mop daily to remove surface dirt and grit. Wash or wet mop weekly. Any beverage spill should be mopped immediately to prevent stain.
- 3) Walk-off mats must be used at all doorways and openings to clean abrasive grit and contaminants from shoes.
- 4) As needed, dust mop your floor to remove dry dirt and debris. Please use dust mop heads that do NOT require a treatment as treatments often leave a film residue. A recommended product is SOLSAN Dust Mop Treatment manufactured by Johnson-Diversey.
- 5) Wet mop any spills and remove any large amounts of dirt or dust ASAP.
- 6) Your GAMECOURT® floor should be damp mopped daily, using a white cotton towel dampened with water, but not wet. Rinse the towel every few passes or as needed. To combat tougher dirt, add a neutral floor cleaner (PH of 7.0 - 7.5) into the water. A recommended product is PROFIL Oil & Grease Remover manufactured by Johnson-Diversey.
- 7) For occasional cleaning, a low speed floor scrubber (175 - 350 rpm), either single disc or an automatic scrubber may be used. Use a neutral or citrus based cleaner (PH of 12 or lower) diluted as per manufacturer's instructions. Use a RED floor pad or a scrub brush. A recommended product is PROFIL Oil & Grease Remover manufactured by Johnson-Diversey. Do not use an automatic scrubber on your new floor for 30 days.
- 8) To remove scuff marks from black soled shoes, use a clean towel that is dampened with a ready-to-use citrus based or butyl based cleaner and wipe clean. Thoroughly rinse the floor with clean water after removing scuff marks.
- 9) Do not use spikes on your GAMECOURT® floor. Do not use abrasive brushes or pads (brown, black, high productivity), steel wool, or solvent to clean your floor. Do not use high-speed floor equipment (1,100 rpm or higher) on your floor.
- 10) Do not use any wax of any kind on your floor. Make sure to check for wax in any cleaning agent or treatment used on your GAMECOURT® floor.
- 11) If you are having trouble cleaning your floor, you may want to apply a clear maintenance coating over the top of your floor. Please note that this maintenance coating will give the floor a higher gloss, but will be easier to clean. Additionally, a maintenance coating should never be applied to your floor until it is extremely clean. A recommended maintenance coating is TASKI VISION MATTE manufactured by Johnson-Diversey. A clear maintenance coat should not be applied until the GAMECOURT® system has cured for 30 days.
- 12) Players and users should wear non-black rubber sole shoes while on the floor.

- 13) Users should not wear sharp studded or sharp pointed shoes when entering the playing area to prevent damages to the GAMECOURT® floor.
- 14) Protect all metal table and chair legs. Do not drag sharp metal objects across the floor.
- 15) When using Johnson-Diversey maintenance products, please contact the manufacturer directly for complete information at 800-827-5427, x130. A local representative will be glad to thoroughly explain and demonstrate the product use and application.