



Moose Sports Surfaces, Ltd.
2257 North Wayne Avenue, Suite 2C
Chicago, Illinois 60614
773.477.4664
773.477.8248 fax
www.mooseports.com

INSTALLATION INSTRUCTIONS
MOOSE PUZZLETILE
Revised 06-02-09

NOTE: THIS GUIDE PROVIDES A FUNDAMENTAL REFERENCE FOR THE INSTALLATION OF THE MOOSE PUZZLETILE SYSTEM. THESE INSTRUCTIONS ARE FOR INFORMATIONAL PURPOSES ONLY. WHILE MOOSE SPORTS SURFACES, LTD. BELIEVES THAT FOLLOWING THESE INSTRUCTIONS WILL RESULT IN THE BEST INSTALLATION, IT MAKES NO WARRANTY OR REPRESENTATION OF ANY NATURE, TYPE, OR DESCRIPTION EXPRESSED, IMPLIED, OR PROVIDED BY LAW RESPECTING THE INSTALLATION PROCESS OR THE RESULTS ACHIEVED. ALTHOUGH VALUABLE INFORMATION IS PROVIDED IN THIS GUIDE, IT IS NOT INTENDED AS A SUBSTITUTE FOR ON SITE TRAINING BY QUALIFIED AND EXPERIENCED PERSONNEL.

1. FLOOR PREPARATION

“IMPORTANT NOTE” - “Loose Lay”

Vapor moisture and pH levels are NOT critical for “loose lay” installations.

This product is intended for indoor use only. Do not use where the flooring will be exposed to fuels, oils, solvents, or other chemicals. Areas to receive flooring should be weather tight and maintained at a minimum uniform temperature of 65°F (18°C) for 48 hours before, during and after the installation.

Surface should be smooth to prevent irregularities, roughness or other defects from telegraphing through the new flooring.

Install MOOSE PUZZLETILE over wood or concrete subfloors, existing resilient flooring such as vinyl, linoleum, laminate, ceramic tile, and wood. MOOSE PUZZLETILE can also be installed over "low pile" carpet using precautionary measures. All carpets have a "nap" in which the fibers run in one direction. The up and down motion of the mat above the carpet will cause it to move in the direction of the nap. To remedy this movement, plastic carpet runners may be installed, spikes down under the MOOSE PUZZLETILE.

2. INSTALLATION PREPARATION – AREA MAT LAYOUT

Mix tiles from several boxes or skids. Install MOOSE PUZZLETILE so that the directional markings stamped on the bottom of the tiles point in the same direction.

For a simple area mat installation, lay down the tiles to the desired length and width and interlock the tabs. For a finished look, trim the interlocking tabs from the mat using a sharp utility knife and a metal straight edge.

3. INSTALLATION PREPARATION – WALL TO WALL LAYOUT

Mix tiles from several boxes or skids. Install MOOSE PUZZLETILE so that the directional markings stamped on the bottom of the tiles point in the same direction.

It is customary to begin tile installations from the center of the room. Measure the width of the area to be covered. Mark the center of the area at two points, one at each end (A and B). Snap a chalk line, line #1, through these two points. Determine the center point of the chalk line. Using a carpenter's square or another method, snap a second chalk line, line

#2, perpendicular (at 90°) to the first line. The lines should intersect at their centers. The area to be covered is now divided into quarters.

Begin the installation at the center of the area where the two lines intersect. MOOSE PUZZLETILE must be installed in the same direction (directional arrows are stamped on the bottom of tiles). Lay whole tiles from left to right along chalk line #1 up to the wall on the opposite side of chalk line #2. The last tile will likely have to be cut to fit against the wall. Cut the last piece to fit against the wall using a metal straight edge and a sharp utility knife. Do not compression fit the tile against the wall. Allow a 1/4" around the perimeter for expansion.

6. DISPOSAL

Dispose all debris and unused material in accordance with all Federal, State and Local statutes.